



SINGAPORE GREEN BUILDING PRODUCT CERTIFICATE

AWARDED TO

Dat Hoa Plastic Company Limited

+84392978109
Vietnam +100000

FOR THE PRODUCT

Pipe & Fittings - Potable Water

PRODUCT BRAND

Dat Hoa Plastic Company Limited

PRODUCT MODEL

Refer to Appendix

THE PRODUCT HAS BEEN ASSESSED ACCORDING
TO THE ASSESSMENT CRITERIA OF SINGAPORE
GREEN BUILDING PRODUCT CERTIFICATION SCHEME.
IT HAS BEEN AWARDED THE RATING:

Director
SGBC Pte Ltd



Certificate Number	Original Issue Date	Revised Date	Valid Till
SGBP 5354	08 July 2024	-	07 July 2026

✓Good ✓✓Very Good ✓✓✓Excellent ✓✓✓✓Leader

The use and reliance on this certificate is subject to the terms and conditions of the Singapore Green Building Product Certification Scheme. Revised certificates may also be issued at the discretion of the Council. The certification status may be verified at the Singapore Green Building Council website (www.sgbc.sg).



SINGAPORE GREEN BUILDING PRODUCT CERTIFICATE

Appendix

Certificate Number: SGBP 5354

Models

uPVC Pipes Inch Series Used For Water Supply: [16x0.8mm PN10, 16x1mm PN13, 21x1.2mm TN, 21x1.4mm PN13, 21x1.6mm PN16, 21x1.7mm PN17, 21x3mm PN32, 27x1.1mm TN, 27x1.4mm PN11, 27x1.8mm PN14, 27x1.9mm PN15, 27x2mm PN16, 27x3mm PN25, 34x1.3mm TN, 34x1.6mm PN10, 34x2.1mm PN13, 34x3mm PN19, 34x4mm PN27, 42x1.35mm TN, 42x1.7mm PN8, 42x2.1mm PN10, 42x2.5mm PN12, 42x3mm PN15, 49x1.45mm TN, 49x1.9mm PN8, 49x2.2mm PN9, 49x2.4mm PN10, 49x2.8mm PN12, 60x1.5mm TN, 60x1.9mm PN6, 60x2.8mm PN9, 60x3mm PN10, 60x3.2mm PN11, 60x4mm PN14, 73x3.3mm PN9, 76x1.8mm TN, 76x2.5mm PN6, 76x3mm PN8, 76x3.3mm PN9, 76x4mm PN11, 76x5mm PN14, 90x1.65mm TN, 90x2.1mm PN4, 90x2.6mm PN6, 90x3mm PN7, 90x3.8mm PN8, 90x4mm PN9, 90x5mm PN12, 90x6mm PN14, 114x2.4mm TN, 114x2.9mm PN6, 114x3.5mm PN7, 114x4mm PN9, 114x4.5mm PN10, 114x5mm PN11, 114x6mm PN13, 114x7mm PN16, 168x3.5mm TN, 168x4.5mm PN6, 168x6.3mm PN9, 168x6.5mm PN10, 168x7.3mm PN11, 168x8.2mm PN12, 220x4mm TN, 220x5.1mm PN5, 220x5.3mm PN6, 220x6.5mm PN7, 220x8mm PN9, 220x8.7mm PN10, 220x9.5mm PN11] uPVC Pipes Metric Series Used for Water Supply: [110x2.45mm TN, 110x3mm PN7, 110x3.6mm PN8, 110x4.2mm PN9, 110x4.5mm PN10, 110x5.3mm PN12.5, 110x6.4mm PN15, 130x3.5mm TN, 130x4mm PN7, 130x4.5mm PN9, 140x3.5mm TN, 140x4mm PN7, 140x5mm PN9, 140x6.5mm PN12, 140x6.7mm PN12.5, 160x4.7mm PN7, 160x6mm PN9, 160x6.2mm PN10, 160x7.7mm PN12.5, 180x7mm PN10, 200x3.5mm TN, 200x4mm PN5, 200x5.9mm PN7, 200x7.3mm PN9, 200x7.7mm PN10, 200x9.6mm PN12.5, 200x11.9mm PN15, 225x6.6mm PN7, 225x10.8mm PN12.5, 250x3.9mm TN, 250x6.2mm PN6, 250x7.3mm PN7, 250x11.9mm PN12.5, 280x8.2mm PN7, 280x10.7mm PN9, 280x13.4mm PN12.5, 315x6.2mm TN, 315x8mm PN6, 315x9.2mm PN7, 315x12.1mm PN10, 315x15mm PN12.5, 400x7.8mm TN, 400x9mm PN5, 400x11.7mm PN7, 400x19.1mm PN12.5, 500x14.6mm PN7, 500x23.9mm PN12.5] uPVC pipes CIOD Series Used For Water Supply: [100x6.7mm PN12, 150x9.7mm PN12, 200x9.7mm PN10] uPVC Pipes For Well Drilling: [42x2mm Grey, 42x1.7mm Grey, 49x2mm Grey, 49x1.7mm Grey, 49x1.1mm Grey, 49x1.1mm white, 49x1mm white, 60x2.6mm Grey, 60x2.1mm Grey, 60x1.7mm white, 90x2.8mm Grey, 90x3.2mm Grey, 140x4.5mm Grey] Thick Straight Connector: DN[21, 27, 34, 42, 49, 60, 76, 90, 114] Thick Reducing Connector: DN[27/21, 34/21, 34/27, 42/21, 42/27, 42/34, 60/21, 60/27, 60/34, 60/42, 60/49, 76/34, 76/42, 76/60, 90/21, 90/27, 90/34, 90/42, 90/49, 90/60, 90/76, 114/27, 114/34, 114/42, 114/49, 114/60, 114/76, 114/90, 168/114, 168/140, 220/168] Male Threaded Twin Connector: DN[21, 27, 34] Reducing Twin Connector with Male Threaded: DN[27x21, 34x21, 34x27, 42x34] Male Threaded Connector: DN[21, 27, 34, 42, 49, 60, 76, 90, 114] Female Threaded Connector: DN[21, 27, 34, 42, 49, 60, 76, 90, 114] Thick Reducing Elbow: DN[27/21, 34/21, 34/27, 42/21, 42/27, 42/34, 49/21, 49/27, 49/34, 49/42, 90/49, 90/60, 114/90] Thick 90° Elbow: DN[21, 27, 34, 42, 49, 60, 76, 90, 114, 168] Reducing Connector with Female Threaded: DN[21/27, 21/34, 27/21, 27/34, 34/27] Reducing Connector with Male Threaded: DN[21/27, 21/34, 27/21, 27/34, 34/27, 34/31, 42/27, 42/34, 49/27, 49/34, 49/42, 60/27, 60/34, 64/42, 60/49] Male Threaded Elbow: DN[21, 27, 34, 42, 49] Female Threaded Elbow: DN[21, 27, 34, 42, 49] Reducing Tee with Male Threaded: DN[21/27] Reducing Tee with Female Threaded: DN[21/27] Anti-Clogging Endcap: DN[60, 90, 114, 140, 168] Thick Endcap: DN[21, 27, 34, 42, 49, 60, 76, 90, 114, 140, 168, 220] Thick 45° Elbow: DN[21, 27, 34, 42, 49, 60, 76, 90, 114, 168, 220] Thick Wye Tee: DN[49, 60, 90, 114] Faucet Endcap: DN[21, 27, 34] PVC Unions: DN[21, 27, 34, 42, 49, 60] Reducing Connector with Copper Male Threaded: [DN21, DN27, 21/27] Reducing Connector with Copper Female Threaded: [DN21, DN27, 21/27] Reducing Elbow with Copper Male Threaded: [DN21, DN27, 21/27] Reducing Elbow with Copper Female Threaded: [DN21, DN27, 21/27] Reducing Tee with Copper Female Threaded: [DN21, DN27, 21/27] Reducing Tee with Copper Male Threaded: [DN21, DN27, 21/27] PVC Clamp Saddle:



DN[60/27, 60/34, 76/27, 76/42, 90/27, 90/42, 114/27, 114/42, 114/49, 114/60, 160/34, 168/60, 220/60] Clamp Saddle with Female Threaded: DN[60/27, 90/27, 114/27, 220/27] Flange Adapter: DN[114, 168, 220] Gasket: DN[114, 168, 220] Sand Filter: DN[20] Thin Straight Connector: DN[21, 27, 34, 42, 49, 60, 76, 90, 110, 114] Thin Reducing Connector: DN[27/21, 34/21, 34/27, 42/21, 42/27, 42/34, 49/21, 49/27, 49/34, 49/42, 60/21, 60/27, 60/34, 60/42, 60/49, 76/27, 76/34, 76/42, 76/49, 76/60, 90/27, 90/34, 90/42, 90/49, 90/60, 114/27, 114/34, 114/42, 114/49, 114/60, 114/76, 114/90, 140/90] Thin 90° Elbow: DN[21, 27, 34, 42, 49, 60, 76, 90, 114, 140, 168, 220] Thin Reducing Elbow: DN[42/21, 49/21, 49/27, 49/34, 49/42, 60/27, 60/34, 60/42, 60/49, 90/49, 90/60, 114/60, 114/90] Thin Tee: DN[21, 27, 34, 42, 49, 60, 76, 90, 110, 114, 140, 168] Thin Reducing Tee: DN[27/21, 34/21, 34/27, 60/27, 49/21, 49/27, 49/34, 49/42, 60/21, 60/34, 60/42, 60/49, 90/60, 114/60, 114/90] Curved Wye Tee: DN[49, 60, 90, 114, 140, 168] Reducing Curved Wye Tee: DN[90/60, 144/60, 168/114, 220/114] Check Tee: DN[60, 90, 114] Thin 45° Elbow: DN[21, 27, 34, 42, 49, 60, 90] Thin 45° Elbow: DN[76, 114, 140, 168, 220] Double Plastic Nail Hook: DN[21, 34, 42, 60, 76, 90, 114] Plastic Nail Hook: DN[21, 27, 34, 42, 49, 60, 76, 90, 114] Foot Valve: DN[21, 27, 49] One-way straight lock: DN[34, 42, 60] Tab Endcap: DN[21, 27, 34, 42, 49, 60, 76, 90, 114] PVC S-type Gully Trap: DN[42, 49, 60, 90] 3 Wye Elbow: DN[21, 27, 34] Thin Reducing 45° Wye Tee: DN[90/60, 114/60, 114/90, 140/90, 140/114, 168/114, 220/168] Thin 45° Wye Tee DN[21, 27, 34, 42, 49, 60, 76, 90, 110, 114, 140, 168, 220] High-Grade uPVC Valves: DN[21, 27, 34, 42, 49, 60] uPVC Valves: DN[21, 27, 34, 42, 49, 60]